



Data Center PDU42U Specifications

Meets IEC C13 and C19 specifications, plus high native retention, and UL94V-0 flame rating. PRO2 receptacles have high retention and are compatible with P-Lock type power cords. This product has ...

Match the PDUs input voltage, phase, and current specifications with the power feed of your UPS or facility connection and the requirements of the connected devices.

The document describes specifications for 42U racks and PDUs. It outlines requirements for 175 DC racks, 20 network racks, and 14 telco racks of size 600mm x 1000mm.

Industry-leading, high-density 0U mounted PDU that provides 24, 42 or 48 evenly distributed outlets on a 42U chassis. Its low-profile circuit breakers are flush with the chassis, and its ...

For region-specific product details and variations in specifications, please download the local leaflet or visit the local website. Delta's power distribution units supply regulated power for data centers and ...

Use Vertical eConnect PDUs in data centers and equipment rooms with 42U or higher racks, cabinets and enclosures to provide power connections alongside equipment for higher-density applications.

All 42 outlets provide metering, monitoring and switching for granular power data and precision control of power delivery. The outlets are evenly distributed into six color-coded load banks, each with its own ...

With its universal input, dynamic C39 outlets and global approval, Eaton's universal input rack PDU G4 (UPDU) is a single solution equipped to meet the most diverse data center rack power needs. ...

With the combination of ATEN eco PDU s and eco DC Energy Management Web GUI, a data center is equipped with real-time monitoring, measurement and analysis of energy consumption - with reports ...

Web: <https://prospettivacasa.eu>

