

Small Form-factor Pluggable (SFP) is a compact, hot-pluggable ...

ZEISS" expertise makes it a reliable partner in developing, constructing and manufacturing of precise components, optical modules and systems. With considerable expertise in the high-tech sector and ...

Explore DwyerOmega"s comprehensive range of industrial sensing, monitoring, and control solutions from thermocouples to pressure transducers engineered for ...

Small Form-factor Pluggable (SFP) is a compact, hot-pluggable network interface module format used for both telecommunication and data communications applications. An SFP interface on networking ...

Electro-Optic Modulator Driver from Lucent Technology Gain: 6 dB (Variable) Input Amplitude Swing: 0.05 to 0.4 Vpp Output Amplitude Swing: 3 to 3.5 Vpp

Explore DwyerOmega"s comprehensive range of industrial sensing, monitoring, and control solutions from thermocouples to pressure transducers engineered for precision and reliability.

The SFP 10dB module offers reliable GPON connectivity with proven compatibility across ZTE and Huawei OLT systems, supporting up to 20 km links and featuring precise optical budgets crucial for ...

The input-related noise is very low, a max. noise level of 0.36 fC can be reached including photodiode for an input current range of 200 nA.The max. power ...

Buy Blackmagic Design Mini Converter Optical Fiber 12G-SDI featuring Converts 12G/6G/3G-SDI to Optical Fiber, Supports Signals up to DCI 4K25, Multi-Rate, Bidirectional Capability, Requires ...

Buy Blackmagic Design Mini Converter Optical Fiber 12G-SDI featuring Converts ...

The Optilab EDFA-PA-PM-M Pre-Amp EDFA is a Polarization Maintaining (PM) high-gain module for amplifying low input level signals that is an easy-to-use and cost-efficient solution for photonic ...

Product overview The Cisco &#174; 40GBASE QSFP (Quad Small Form-Factor Pluggable) portfolio offers customers a wide variety of high-density and low-power 40 Gigabit Ethernet ...

The LLF and SLF cards incorporate optical modules with preprogrammed parameters for configuration--only power and high-speed signalling is required. An I2C serial interface is provided to ...

Web: <https://prospettivacasa.eu>

